

ENGINEERING NOTE:

- NEUTRAL MAY BE INSTALLED AT 60" TO MEET EXISTING FIELD CONDITIONS.
- LIGHTING ARRESTOR POSITION IS SHOWN AS A REFERENCE. IT IS TO BE INSTALLED ONLY WHEN DESIGNATED BY ENGINEERING. THIS POSITION IS FOR USE WITHOUT A TRANSFORMER.
- REFERENCE OH-910
- FOR LIGHTING ARRESTOR: 286-04-10010 21" ARM: 285-21-13776

DRAWN BY:	DATE:	APPROVED BY:
GL	3/17/04	
REVISED BY:	DATE:	APPROVED BY:
CY/JC	1/27/15	

TITLE:

SINGLE PHASE DEADEND



STANDARD NO.:

OH - 1280

Construction Standard No.

OH-1280

Title: SINGLE PHASE DEADEND Rev. Date: 1/21/2015

Pic#	Description	IBM NO.	Qty
1	INSULATOR DEAD END 3.5" X 12-1/2" LENGTH CHANCE #C654-3015	286-42-26020	1
2	INSULATOR SPOOL TYPE SECONDARY	286-42-23310	1
3	1 PT RACK GALV 1-1/2" X 1/2" X 1/8" CLEVIS	285-39-14039	1
4	NUT 5/8" OVAL EYE	285-08-56640	1
5	BOLT MACHINE 5/8" X 14" W/ NUT	285-08-10788	1
6	CLAMP DEADEND STRAIGHT LINE ALUM ACSR .470" TO .198", 2/O TO #6	285-13-16395	1
7	WASHER SQUARE 5/8" 250/BX	285-08-15320	2
8	WASHER SPRING DOUBLE COIL 5/8" 500/BX	285-08-85430	2

