



SPOOL POSITION WHEN USING DOWN GUY

GENERAL CONSTRUCTION NOTE:

1. STANDARD 5/8" SQUARE NUTS ISSUED WITH DA BOLTS, OE BOLTS, MH BOLTS AND STEEL INSULATOR PINS SHOULD BE USED FOR LOCK (JAM) NUTS.
2. DISCARD SQUARE WASHER AND LOCK (MF) NUT ISSUED WITH STEEL INSULATOR PIN, USE ISSUED NUT WASHER IN PLACE OF SQUARE WASHER.

A	#6-4/0
B	336/477

TITLE:
THREE PHASE DOUBLE
DEAD END ON
5' FIBER ARM

GARLAND
POWER & LIGHT

STANDARD NO.:
OH-1610

DRAWN BY: DATE: APPROVED BY:
LG 3/17/04 CP

REVISED BY: DATE: APPROVED BY:

CONSTRUCTION STANDARD NO. : OH-1610A

TITLE: 3 PHASE DBL D.E. ON 5' FIBER ARM 6-4/0

REV. DATE: 5/21/2002

PIC. #	DESCRIPTION	IBM NO.	QTY.
1	CROSSARM, 60" x 3" FIBERGLASS (FOR DEAD ENDING CONDUCTORS)	285-21-13755	1
2	PIN POLE TOP, FIBERGLASS, CONTINENTAL GRP-58M-21, 1" THRDS	285-21-13825	1
3	INSULATOR DEAD END 3.5" X 12-1/2" LENGTH CHANCE #C654-3015	286-42-26020	6
4	INSULATOR PIN TYPE 15KV	286-42-25100	3
5	PIN STEEL 5/8" X 5-3/4" W/NUTS	285-39-10246	2
6	INSULATOR SPOOL TYPE SECONDARY	286-42-23310	2
7	1 PT RACK GALV 1-1/2" X 1/2" X 1/8" CLEVIS	285-39-14039	2
8	BOLT DOUBLE ARMING 5/8" X 14"	285-08-21552	1
9	BOLT WASHER HEAD 5/8" X 14" W/ WASHER NUT	285-08-96926	3
10	NUT WASHER 5/8" THREAD JOSLYN	285-08-14674	6
11	CLAMP DEADEND STRAIGHT LINE ALUM ACSR .470" TO .198", 2/O TO #6	285-13-16395	6
12	NUT 5/8" OVAL EYE	285-08-56640	2
13	BOLT DOUBLE ARMING 5/8" X 16"	285-08-21554	1

CONSTRUCTION STANDARD NO. : OH-1610B**TITLE: 3 PHASE DBL D.E. ON 5' FIBER ARM 336-477**

REV. DATE: 5/21/2002

PIC. #	DESCRIPTION	IBM NO.	QTY.
1	CROSSARM, 60" x 3" FIBERGLASS (FOR DEAD ENDING CONDUCTORS)	285-21-13755	1
2	PIN POLE TOP, FIBERGLASS, CONTINENTAL GRP-58M-21, 1" THRDS	285-21-13825	1
3	INSULATOR DEAD END 3.5" X 12-1/2" LENGTH CHANCE #C654-3015	286-42-26020	6
4	INSULATOR PIN TYPE 15KV	286-42-25100	3
5	PIN STEEL 5/8" X 5-3/4" W/NUTS	285-39-10246	2
8	BOLT DOUBLE ARMING 5/8" X 14"	285-08-21552	1
9	BOLT WASHER HEAD 5/8" X 14" W/ WASHER NUT	285-08-96926	3
10	NUT WASHER 5/8" THREAD JOSLYN	285-08-14674	6
11	CLAMP DEADEND STRAIGHT LINE .464" TO .860"	285-13-16390	8
12	NUT 5/8" OVAL EYE	285-08-56640	4
13	BOLT DOUBLE ARMING 5/8" X 16"	285-08-21554	1